

Crash when deleting a column from attribute table

Status:	Closed	
Priority:	Severe/Regression	
Assignee:		
Category:	Attribute table	
Affected QGIS version:	master	Regression?: No
Operating System:		Easy fix?: No
Pull Request or Patch supplied:	no	Resolution:
Crashes QGIS or corrupts data:	yes	Copied to github as #: 19538

When I try to delete attribute from layer attribute table QGIS crashes. Tested in latest master (11be64d) with shapefiles under Linux. Here is console output:

```
[New LWP 14483]
[New LWP 14482]
[New LWP 14481]
[New LWP 14479]
[New LWP 14471]
[New LWP 14470]
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib64/libthread_db.so.1".
0x00007f049e2df317 in waitpid () from /lib64/libc.so.6
Traceback (most recent call last):
  File "/usr/share/gdb/auto-load/usr/lib64/libgobject-2.0.so.0.3200.4-gdb.py", line 9, in <module>
    from gobject import register
File "/usr/share/glib-2.0/gdb/gobject.py", line 3, in <module>
    import gdb.backtrace
ImportError: No module named backtrace
[Current thread is 1 (Thread 0x7f04a619c7c0 (LWP 14468))]
#0 0x00007f049e2df317 in waitpid () from /lib64/libc.so.6
No symbol table info available.
#1 0x0000000000513965 in qgisCrash (signal=<optimized out>) at /home/alex/devel/cpp/qgis/src/app/main.cpp:292
   status = <optimized out>
   pidstr = "--pid=14468\000\377\177\000\000y\225(\241\004\177\000\000\000\000\000\000\000\000\000\"
   gdbpid = <optimized out>
   exename = 
"/data/devel/cpp/qgis/build/output/bin/qgis\000\061\377\177\000\000X\373\323\006\000\000\000\000\\\?\277\240\004\177\000\\
\177\000\000\b\360\a1\377\177\000\000`\364\xa1\377\177\000\000\300+/\a\000\000\000\000\340\266m\a\000\000\000\000\
000\000\000\364\xa1\377\177\000\000\267\243\377\240\004\177\000\000\000\000\000\000\026\", '\000' <repeats
27 times>\`'\340,\355Q/a\000\000\000\000\001\000\000\000\001\", '\000' <repeats 19 times>\`'\300,
+/a\000\000\000\000\260\320\177\002\000\000\000\000\300\000\000\000\000\000\000\000\002\000\000\000\000\000\000\001\000\300+/\a\000\000\000\000\364\xa1\377\177\000\000\260\320\177\002\000\000\000\000\364\xa1\377\177\
1\377\177\000\000\340\364\xa1\377\177\000\000\\\?\277\240\004\177\000\000\300+/\a\000\000\000\000"...
   len = <optimized out>
#2 <signal handler called>
No symbol table info available.
#3 0x000000000754fcd0 in ?? ()
No symbol table info available.
#4 0x00007f04a1875b3a in QObject::connect(QObject const*, char const*, QObject const*, char const*, Qt::ConnectionType) ()
```

```

from /usr/lib64/qt/lib/libQtCore.so.4
No symbol table info available.
#5 0x00007f04a253f172 in QgsAttributeForm::init (this=this@entry=0x6e5efb0) at
/home/alex/devel/cpp/qgis/src/gui/qgsattributeform.cpp:452
    formWidget = <optimized out>
    __FUNCTION__ = "init"
#6 0x00007f04a254048d in QgsAttributeForm::onAttributeDeleted (this=0x6e5efb0, idx=<optimized out>) at
/home/alex/devel/cpp/qgis/src/gui/qgsattributeform.cpp:285
No locals.
#7 0x00007f04a265c5b7 in QgsAttributeForm::qt_static_metacall (_o=0x6e5efb0, _c=<optimized out>, _id=11,
_a=0x7fff3107fd30) at /home/alex/devel/cpp/qgis/build/src/gui/moc_qgsattributeform.cxx:85
    _t = 0x6e5efb0
#8 0x00007f04a1871ebf in QMetaObject::activate(QObject*, QMetaObject const*, int, void**) () from
/usr/lib64/qt/lib/libQtCore.so.4
No symbol table info available.
#9 0x00007f04a2f90661 in QgsVectorLayer::attributeDeleted (this=this@entry=0x69e27b0, _t1=2) at
/home/alex/devel/cpp/qgis/build/src/core/moc_qgsvectorlayer.cxx:337
    _a = {0x0, 0x7fff3107fd2c}
#10 0x00007f04a2f90d8e in QgsVectorLayer::qt_static_metacall (_o=0x69e27b0, _c=<optimized out>, _id=<optimized out>,
_a=0x7fff3107fed0) at /home/alex/devel/cpp/qgis/build/src/core/moc_qgsvectorlayer.cxx:201
    _t = 0x69e27b0
#11 0x00007f04a1871ebf in QMetaObject::activate(QObject*, QMetaObject const*, int, void**) () from
/usr/lib64/qt/lib/libQtCore.so.4
No symbol table info available.
#12 0x00007f04a2f91221 in QgsVectorLayerEditBuffer::attributeDeleted (this=<optimized out>, _t1=2) at
/home/alex/devel/cpp/qgis/build/src/core/moc_qgsvectorlayereditbuffer.cxx:185
    _a = {0x0, 0x7fff3107fecc}
#13 0x00007f04a2e6b609 in QgsVectorLayerUndoCommandDeleteAttribute::redo (this=0x6d5a940) at
/home/alex/devel/cpp/qgis/src/core/qgsvectorlayerundocommand.cpp:422
No locals.
#14 0x00007f04a123f673 in QUndoStack::push(QUndoCommand*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.
#15 0x00007f04a2e4fa43 in QgsVectorLayerEditBuffer::deleteAttribute (this=0x7a5d4e0, index=2) at
/home/alex/devel/cpp/qgis/src/core/qgsvectorlayereditbuffer.cpp:234
    origin = QgsFields::OriginProvider
    originIndex = -1584184662
#16 0x00007f04a2e49282 in QgsVectorLayer::deleteAttributes (this=0x69e27b0, attrs=...) at
/home/alex/devel/cpp/qgis/src/core/qgsvectorlayer.cpp:2139
    attr = <optimized out>
    _container_ = {c = {{p = {static shared_null = {ref = {_q_value = 7410}, alloc = 0, begin = 0, end = 0, sharable = 1, array =
{0x0}}, d = 0x73017b0}, d = 0x73017b0}}, brk = 0, i = {i = 0x73017c8}, e = {i = 0x73017d0}}
    deleted = <optimized out>
#17 0x000000000059a917 in QgsAttributeTableDialog::on_mRemoveAttribute_clicked (this=0x772f980) at
/home/alex/devel/cpp/qgis/src/app/qgsattributetabledialog.cpp:630
    attributes = {{p = {static shared_null = {ref = {_q_value = 7410}, alloc = 0, begin = 0, end = 0, sharable = 1, array = {0x0}}, d =
0x785a4e0}, d = 0x785a4e0}}
    masterModel = 0x2f41390
    dialog = {<QDialog> = {<No data fields>, <Ui::QgsDelAttrDialogBase> = {<Ui_QgsDelAttrDialogBase> = {gridLayout =
0x76fabe0, listBox2 = 0x78dc050, buttonBox = 0x6a24bc0}, <No data fields>, static staticMetaObject = {d = {superdata =
0x7f04a16a15a0 <QDialog::staticMetaObject>, stringdata = 0x937960 <qt_meta_stringdata_QgsDelAttrDialog>
"QgsDelAttrDialog", data = 0x937980 <qt_meta_data_QgsDelAttrDialog>, extradata = 0xde6b80
<QgsDelAttrDialog::staticMetaObjectExtraData>}}, static staticMetaObjectExtraData = {objects = 0x0, static_metacall = 0x860d00
<QgsDelAttrDialog::qt_static_metacall(QObject*, QMetaObject::Call, int, void**)>}}

```

#18 0x000000000085e4f1 in QgsAttributeTableDialog::qt_static_metacall (_o=_o@entry=0x772f980, _c=_c@entry=QMetaObject::InvokeMetaMethod, _id=12, _a=_a@entry=0x7fff310803a0) at /home/alex/devel/cpp/qgis/build/src/app/moc_qgsattributetabledialog.cxx:118
_t = 0x772f980

#19 0x000000000085e69b in QgsAttributeTableDialog::qt_metacall (this=0x772f980, _c=QMetaObject::InvokeMetaMethod, _id=<optimized out>, _a=0x7fff310803a0) at /home/alex/devel/cpp/qgis/build/src/app/moc_qgsattributetabledialog.cxx:175
No locals.

#20 0x00007f04a1872083 in QMetaObject::activate(QObject*, QMetaObject const*, int, void**) () from /usr/lib64/qt/lib/libQtCore.so.4
No symbol table info available.

#21 0x00007f04a1257772 in QAbstractButton::clicked(bool) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#22 0x00007f04a0fab95e in ?? () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#23 0x00007f04a0fac190 in ?? () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#24 0x00007f04a0fac3fc in QAbstractButton::mouseReleaseEvent(QMouseEvent*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#25 0x00007f04a106634a in QToolButton::mouseReleaseEvent(QMouseEvent*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#26 0x00007f04a0c436a0 in QWidget::event(QEvent*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#27 0x00007f04a0bf3f5c in QApplicationPrivate::notify_helper(QObject*, QEvent*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#28 0x00007f04a0bf8c3b in QApplication::notify(QObject*, QEvent*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#29 0x00007f04a2c5c6a3 in QgsApplication::notify (this=0x7fff31082150, receiver=0x71df620, event=0x7fff31080ca0) at /home/alex/devel/cpp/qgis/src/core/qgsapplication.cpp:243
done = true
__FUNCTION__ = "notify"

#30 0x00007f04a185cabe in QCoreApplication::notifyInternal(QObject*, QEvent*) () from /usr/lib64/qt/lib/libQtCore.so.4
No symbol table info available.

#31 0x00007f04a0bf4d9b in QApplicationPrivate::sendMouseEvent(QWidget*, QMouseEvent*, QWidget*, QWidget*, QWidget**, QPointer<QWidget>&, bool) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#32 0x00007f04a0c6feb4 in ?? () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#33 0x00007f04a0c6e7b1 in QApplication::x11ProcessEvent(_XEvent*) () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#34 0x00007f04a0c943e2 in ?? () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#35 0x00007f049b2ddc35 in g_main_context_dispatch () from /usr/lib64/libglib-2.0.so.0
No symbol table info available.

#36 0x00007f049b2ddf68 in ?? () from /usr/lib64/libglib-2.0.so.0
No symbol table info available.

#37 0x00007f049b2de024 in g_main_context_iteration () from /usr/lib64/libglib-2.0.so.0
No symbol table info available.

#38 0x00007f04a188ac16 in QEventDispatcherGlib::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib64/qt/lib/libQtCore.so.4
No symbol table info available.

#39 0x00007f04a0c9406e in ?? () from /usr/lib64/qt/lib/libQtGui.so.4
No symbol table info available.

#40 0x00007f04a185b80f in QEventLoop::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () from

/usr/lib64/qt/lib/libQtCore.so.4

No symbol table info available.

#41 0x00007f04a185ba98 in QEventLoop::exec(QFlags<QEventLoop::ProcessEventsFlag>) () from

/usr/lib64/qt/lib/libQtCore.so.4

No symbol table info available.

#42 0x00007f04a1860738 in QApplication::exec() () from /usr/lib64/qt/lib/libQtCore.so.4

No symbol table info available.

#43 0x000000000050d8a0 in main (argc=1, argv=0x2853e10) at /home/alex/devel/cpp/qgis/src/app/main.cpp:1017

qgistor = <incomplete type>

mySnapshotHeight = 600

args = {<QList<QString>> = {{p = {static shared_null = {ref = {_q_value = 7410}, alloc = 0, begin = 0, end = 0, sharable = 1, array = {0x0}}, d = 0x27e3130}, d = 0x27e3130}}, <No data fields>}

myApp = {<QApplication> = {<No data fields>}, static staticMetaObject = {d = {superdata = 0x7f04a168b3e0 <QApplication::staticMetaObject>, stringdata = 0x7f04a2ffdf80 <qt_meta_stringdata_QgsApplication> "QgsApplication", data = 0x7f04a2ffdfde0 <qt_meta_data_QgsApplication>, extradata = 0x7f04a33084e0 <QgsApplication::staticMetaObjectExtraData>}, static staticMetaObjectExtraData = {objects = 0x0, static_metacall = 0x7f04a2f89f30 <QgsApplication::qt_static_metacall(QObject*, QMetaObject::Call, int, void**)>}, static QGIS_ORGANIZATION_NAME = 0x7f04a2ff1b00 "QGIS", static QGIS_ORGANIZATION_DOMAIN = 0x7f04a2fa8de6 "qgis.org", static QGIS_APPLICATION_NAME = 0x7f04a2fa8de0 "QGIS2", static mFileOpenEventReceiver20500 = 0x28b3eb0, static mFileOpenEventList20500 = {<QList<QString>> = {{p = {static shared_null = {ref = {_q_value = 7410}, alloc = 0, begin = 0, end = 0, sharable = 1, array = {0x0}}, d = 0x7f04a1bb5b40 <QListData::shared_null>}, d = 0x7f04a1bb5b40 <QListData::shared_null>}}, <No data fields>}, static mPrefixPath20500 = {static null = <No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x7f04a1bb5c20 <QString::shared_null>, static codecForCStrings = 0x0}, static mPluginPath20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x28355d0, static codecForCStrings = 0x0}, static mPkgDataPath20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x2836ae0, static codecForCStrings = 0x0}, static mLibraryPath20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x2835770, static codecForCStrings = 0x0}, static mLibexecPath20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x2835800, static codecForCStrings = 0x0}, static mThemeName20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x2a153e0, static codecForCStrings = 0x0}, static mDefaultSvgPaths20500 = {<QList<QString>> = {{p = {static shared_null = {ref = {_q_value = 7410}, alloc = 0, begin = 0, end = 0, sharable = 1, array = {0x0}}, d = 0x287ed20}, d = 0x287ed20}}, <No data fields>}, static mSystemEnvVars20500 = {{d = 0x2848160, e = 0x2848160}}, static mConfigPath20500 = {static null = <No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x28356e0, static codecForCStrings = 0x0}, static mRunningFromBuildDir20500 = true, static mBuildSourcePath20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x2836ae0, static codecForCStrings = 0x0}, static mBuildOutputPath20500 = {static null = <same as static member of an already seen type>, static shared_null = <same as static member of an already seen type>, static shared_empty = <same as static member of an already seen type>, d = 0x27ab090, static codecForCStrings = 0x0}, static mGdalSkipList20500 = {<QList<QString>> = {{p = {static shared_null = {ref = {_q_value = 7410}, alloc = 0, begin = 0, end = 0, sharable = 1, array = {0x0}}, d = 0x7f04a1bb5b40 <QListData::shared_null>}, d = 0x7f04a1bb5b40 <QListData::shared_null>}}, <No data fields>}, static mMaxThreads20500 = -1}

myLocaleOverrideFlag = <optimized out>

```

__FUNCTION__ = "main"
mySnapshotFileName = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x7f04a1bb5c00 <QString::shared_empty>, static codecForCStrings = 0x0}
myHideSplash = false
myRestorePlugins = true
myTranslationCode = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x2847e30, static codecForCStrings = 0x0}
customizationfile = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x7f04a1bb5c20 <QString::shared_null>, static codecForCStrings = 0x0}
style = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x284fb40, static codecForCStrings = 0x0}
qttor = <incomplete type>
myPixmap = <incomplete type>
myInitialExtent = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x27b44a0, static codecForCStrings = 0x0}
mySettings = <incomplete type>
i18nPath = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x28a1ed0, static codecForCStrings = 0x0}
myLocale = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x7f04a1bb5c20 <QString::shared_null>, static codecForCStrings = 0x0}
qgis = 0x28b3eb0
retval = <optimized out>
optionpath = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a <QString::shared_empty+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d = 0x7f04a1bb5c20 <QString::shared_null>, static codecForCStrings = 0x0}
customizationsettings = <optimized out>
systemEnvVars = {{d = 0x2848160, e = 0x2848160}}
myRestoreDefaultWindowState = false
pythonfile = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data = 0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletext = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0,

```

```

array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a
<QString::shared_empty+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d =
0x7f04a1bb5c20 <QString::shared_null>, static codecForCStrings = 0x0}
    myUseGuiFlag = <optimized out>
    myUserLocale = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data =
0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0,
array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a
<QString::shared_empty+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d =
0x282b680, static codecForCStrings = 0x0}
    mySplashPath = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data =
0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0,
array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a
<QString::shared_empty+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d =
0x2845bb0, static codecForCStrings = 0x0}
    mySnapshotWidth = 800
    myCustomization = <optimized out>
    configpath = {static null = {<No data fields>}, static shared_null = {ref = {_q_value = 12138}, alloc = 0, size = 0, data =
0x7f04a1bb5c3a <QString::shared_null+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0,
array = {0}}, static shared_empty = {ref = {_q_value = 465}, alloc = 0, size = 0, data = 0x7f04a1bb5c1a
<QString::shared_empty+26>, clean = 0, simpletex = 0, righttoleft = 0, asciiCache = 0, capacity = 0, reserved = 0, array = {0}}, d =
0x7f04a1bb5c20 <QString::shared_null>, static codecForCStrings = 0x0}
    useCustomVars = <optimized out>
    mypSplash = 0x2853e10

```

Associated revisions

Revision 35936084 - 2014-09-22 08:47 AM - Matthias Kuhn

Restore buttonbox visibility after attribute form reload

Followup febe37de

Fix #11229

Fix #11194

History

#1 - 2014-09-19 11:56 AM - Maxim Dubinin

same thing under Win

#2 - 2014-09-19 06:04 PM - Nyal Dawson

Adding a column also results in a similar crash.

#3 - 2014-09-20 03:10 AM - Pedro Venâncio

Nyal Dawson wrote:

|

| Adding a column also results in a similar crash.

Yes, this was already reported and happens both with shapefiles and Postgis layers: #11194

#4 - 2014-09-21 11:51 PM - Matthias Kuhn

- *Status changed from Open to Closed*

Fixed in changeset commit:"35936084ff9c6ff912611bab471a3ddf20aa906b".