

## QGIS Application - Bug report #1182

### Project 'dirty' flag not set for loading layers (and other operations)

2008-07-25 02:59 AM - barryrowlingson -

<b>Status:</b>	Closed	
<b>Priority:</b>	Low	
<b>Assignee:</b>	Tim Sutton	
<b>Category:</b>	Project Loading/Saving	
<b>Affected QGIS version:</b>		<b>Regression?:</b> No
<b>Operating System:</b>	All	<b>Easy fix?:</b> No
<b>Pull Request or Patch supplied:</b>		<b>Resolution:</b> fixed
<b>Crashes QGIS or corrupts data:</b>		<b>Copied to github as #:</b> 11242
<b>Description</b>		
<p>Start Qgis, load a layer (vector or raster), then do File... Exit. Qgis quits without prompting to save the project.</p> <p>Various other operations don't set the project dirty flag - for example changing the symbology of a point layer. Things that do call the dirty flag are here:</p> <p><a href="http://doc.qgis.org/classQgsProject.html#3905fa4118ae850dbdb920f8805c24bbc1a">http://doc.qgis.org/classQgsProject.html#3905fa4118ae850dbdb920f8805c24bbc1a</a></p> <p>Things that change the project should call: <code>[[QgsProject]]::instance()-&gt;dirty(true)</code></p> <p>( Python plugins should do: <code>[[QgsProject]].instance().dirty(True)</code> )</p>		

#### History

##### #1 - 2008-07-25 04:58 AM - Tim Sutton

- Resolution set to fixed
- Status changed from Open to Closed

Fixed in commit:5133fc7e (SVN r8898), commit:96a66727 (SVN r8899) and .

I set the dirty flag in qgisapp whenever a layer is added (commit:5133fc7e (SVN r8898)), removed (), and in vector and raster properties when apply() is called (commit:96a66727 (SVN r8899)).

##### #2 - 2009-08-22 12:57 AM - Anonymous

Milestone Version 1.0.0 deleted