

QGIS Application - Bug report #13507

Trying to access options menu crashes

2015-10-04 04:42 AM - Johannes Kroeger

Status:	Closed	
Priority:	Severe/Regression	
Assignee:	Larry Shaffer	
Category:	Authentication system	
Affected QGIS version:	master	Regression?: No
Operating System:	Ubuntu	Easy fix?: No
Pull Request or Patch supplied:	No	Resolution:
Crashes QGIS or corrupts data:	Yes	Copied to github as #: 21551
Description		
If I click Settings -> Options, QGIS will crash. See attached backtrace. I am on Archlinux, 64 bit. Built master just now, 28958. Program received signal SIGSEGV, Segmentation fault. 0x00007ffff6ebc538 in QgsAuthConfigEditor::setShowUtilitiesButton (this=<optimized out>, show=false) at /home/qwerty/src/qgis/src/gui/auth/qgsauthconfigeditor.cpp:177 177 btnAuthUtilities->setVisible(show); (gdb) bt #0 0x00007ffff6ebc538 in QgsAuthConfigEditor::setShowUtilitiesButton (this=<optimized out>, show=false) at /home/qwerty/src/qgis/src/gui/auth/qgsauthconfigeditor.cpp:177 #1 0x00007ffff6ec54e2 in QgsAuthEditorWidgets::QgsAuthEditorWidgets (this=0x43a2510, parent=<optimized out>) at /home/qwerty/src/qgis/src/gui/auth/qgsautheditorwidgets.cpp:98 #2 0x00007ffff78098b7 in Ui_QgsOptionsBase::setUpUi (this=this@entry=0x3ea5088, QgsOptionsBase=QgsOptionsBase@entry=0x3ea5010) at /home/qwerty/src/qgis/build/src/app/./ui/ui_qgsoptionsbase.h:3257 #3 0x00007ffff77db333 in QgsOptions::QgsOptions (this=0x3ea5010, parent=<optimized out>, fl=...) at /home/qwerty/src/qgis/src/app/qgsoptions.cpp:75 #4 0x00007ffff76115a2 in QgisApp::showOptionsDialog (this=this@entry=0x94bbc0, parent=parent@entry=0x94bbc0, currentPage=...) at /home/qwerty/src/qgis/src/app/qgisapp.cpp:7912 #5 0x00007ffff7612461 in QgisApp::options (this=this@entry=0x94bbc0) at /home/qwerty/src/qgis/src/app/qgisapp.cpp:7902 #6 0x00007ffff79d6eb5 in QgisApp::qt_static_metacall (_o=0x94bbc0, _c=<optimized out>, _id=<optimized out>, _a=0x7fffffc9d0) at /home/qwerty/src/qgis/build/src/app/moc_qgisapp.cxx:847 #7 0x00007ffff5cc7630 in QMetaObject::activate(QObject*, QMetaObject const*, int, void**) () from /usr/lib/libQtCore.so.4 #8 0x00007ffff4fda402 in QAction::triggered(bool) () from /usr/lib/libQtGui.so.4 #9 0x00007ffff4fdb763 in QAction::activate(QAction::ActionEvent) () from /usr/lib/libQtGui.so.4 #10 0x00007ffff5439b0d in ?? () from /usr/lib/libQtGui.so.4 #11 0x00007ffff543df09 in ?? () from /usr/lib/libQtGui.so.4 #12 0x00007ffff5036c20 in QWidget::event(QEvent*) () from /usr/lib/libQtGui.so.4 #13 0x00007ffff544217b in QMenu::event(QEvent*) () from /usr/lib/libQtGui.so.4 #14 0x00007ffff4fe039c in QApplicationPrivate::notify_helper(QObject*, QEvent*) () from /usr/lib/libQtGui.so.4 #15 0x00007ffff4fe73b6 in QApplication::notify(QObject*, QEvent*) () from /usr/lib/libQtGui.so.4 #16 0x00007ffff632cdab in QgsApplication::notify (this=0x7fffffd070, receiver=0xa06ad0, event=0x7fffffd0c0) at /home/qwerty/src/qgis/src/core/qgsapplication.cpp:265 #17 0x00007ffff5cb355d in QCoreApplication::notifyInternal(QObject*, QEvent*) () from /usr/lib/libQtCore.so.4 #18 0x00007ffff4fe69bd in QApplicationPrivate::sendMouseEvent(QWidget*, QMouseEvent*, QWidget*, QWidget*, QWidget**, QPointer<QWidget>&, bool) () from /usr/lib/libQtGui.so.4		

#19 0x00007ffff506232c in ?? () from /usr/lib/libQtGui.so.4
#20 0x00007ffff506036d in QApplication::x11ProcessEvent(_XEvent*) () from /usr/lib/libQtGui.so.4
#21 0x00007ffff50892e2 in ?? () from /usr/lib/libQtGui.so.4
#22 0x00007fffd2789fd in g_main_context_dispatch () from /usr/lib/libglib-2.0.so.0
#23 0x00007fffd278ce0 in ?? () from /usr/lib/libglib-2.0.so.0
#24 0x00007fffd278d8c in g_main_context_iteration () from /usr/lib/libglib-2.0.so.0
#25 0x00007ffff5ce3854 in QEventDispatcherGlib::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib/libQtCore.so.4
#26 0x00007ffff50893b6 in ?? () from /usr/lib/libQtGui.so.4
#27 0x00007ffff5cb1dd1 in QEventLoop::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib/libQtCore.so.4
#28 0x00007ffff5cb2145 in QEventLoop::exec(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib/libQtCore.so.4
#29 0x00007ffff5cb7af9 in QCoreApplication::exec() () from /usr/lib/libQtCore.so.4
#30 0x000000000407097 in main (argc=3, argv=<optimized out>) at /home/qwerty/src/qgis/src/app/main.cpp:1229

Related issues:

Related to QGIS Application - Bug report # 13454: 2.11 Authentification Syste...

Closed

2015-09-29

Associated revisions

Revision 6a7332f4 - 2015-10-06 11:36 PM - Larry Shaffer

[auth] Fix #13507; ensure auth widgets are disabled if auth system is

History

#1 - 2015-10-04 09:38 AM - Matthias Kuhn

- Priority changed from High to Severe/Regression
- Assignee set to Larry Shaffer

Seems to be related to the authentication configuration

#2 - 2015-10-06 12:56 AM - Jürgen Fischer

- Category set to Authentication system

#3 - 2015-10-06 08:59 AM - Larry Shaffer

Hi Johannes,

I am working on a fix right now, but would like a bit more information. Do you get the notification dialog when QGIS starts up, noting that the "Authentication System is DISABLED"?

#4 - 2015-10-06 12:36 PM - Saber Razmjooei

Have you tried:
pacman -S qca-openssl

It seems to be related to #13454

#5 - 2015-10-06 02:38 PM - Larry Shaffer
- Status changed from Open to Closed

Fixed in changeset commit:"6a7332f4777099c84a8f24c6f052568d77bbdd79".

Files

bt.log	3.69 KB	2015-10-04	Johannes Kroeger
--------	---------	------------	------------------