

## QGIS Application - Feature request #13615

### Head/Tail Breaks

2015-10-15 06:12 PM - Spencer Gardner

<b>Status:</b>	Open	<b>Resolution:</b> <b>Copied to github as #:</b> 21653
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>	Unknown	
<b>Pull Request or Patch supplied:</b>	No	
<b>Easy fix?:</b>	No	
<b>Description</b>		
<p>Has there been any discussion about implementing head/tail breaks as a choropleth categorization on layers? It seems like it wouldn't be difficult to implement. Here's a paper that introduces the concept:</p> <p><a href="http://arxiv.org/pdf/1209.2801.pdf">http://arxiv.org/pdf/1209.2801.pdf</a></p>		

#### History

##### #1 - 2016-09-05 07:05 AM - Ding Martin

Hi

There is already a related implementation in Axwoman 6.3 (function name "HT mapping", <http://fromto.hig.se/~bjg/axwoman/>) about using head/tail breaks for choropleth maps, and for point and polyline feature as well.

Martin

##### #2 - 2017-05-01 12:47 AM - Giovanni Manghi

- *Easy fix? set to No*

##### #3 - 2017-09-22 10:07 AM - Jürgen Fischer

- *Category set to Unknown*