

## QGIS Application - Bug report #13710

### postgis view layer with compound key lost on project reload

2015-10-29 08:16 AM - Jochen Huber

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Jürgen Fischer	
<b>Category:</b>	Data Provider/PostGIS	
<b>Affected QGIS version:</b>	master	<b>Regression?:</b> No
<b>Operating System:</b>	Windows (OSgeo4W)	<b>Easy fix?:</b> No
<b>Pull Request or Patch supplied:</b>	No	<b>Resolution:</b>
<b>Crashes QGIS or corrupts data:</b>	No	<b>Copied to github as #:</b> 21737
<b>Description</b>		
<p>With QGIS 2.12, it is possible to load Postgis views with compound primary keys - a very useful feature. The Layers can be visualized and the attribute table is displayed correctly.</p> <p>However, when loading a saved project file with such a layer, the layer is shown as defective and has to be manually added once again. Postgis Layers for views with a single key field are loaded correctly.</p> <p>An example project file with two sample layers is attached. Layer "test" (one pk field) loads correctly, layer "ViewGwStichtag" (two pk fields, both of type 'character varying') does not.</p>		

#### Associated revisions

##### Revision daa65109 - 2015-11-01 03:53 PM - Jürgen Fischer

postgres provider: quote compound key columns in uri (fixes #13710)

##### Revision fa47c963 - 2015-11-01 09:47 PM - Jürgen Fischer

postgres provider: quote compound key columns in uri (fixes #13710)

(cherry picked from commit daa6510970e9afbc4d41d28e0c94b4f238eb372d)

#### History

##### #1 - 2015-11-01 06:57 AM - Jürgen Fischer

- Status changed from Open to Closed

Fixed in changeset commit:"daa6510970e9afbc4d41d28e0c94b4f238eb372d".

##### #2 - 2016-10-13 01:55 AM - Sandro Santilli

This change broke drag & drop copying of views from DBManager, see #15226

#### Files

test.qgs	23 KB	2015-10-29	Jochen Huber
----------	-------	------------	--------------