

QGIS Application - Bug report #14340

layer definition file load error

2016-02-20 12:35 AM - Norihito Takahashi

Status:	Closed	
Priority:	Normal	
Assignee:	Jürgen Fischer	
Category:	Unknown	
Affected QGIS version:	2.10.1	Regression?: No
Operating System:		Easy fix?: No
Pull Request or Patch supplied:	No	Resolution: fixed/implemented
Crashes QGIS or corrupts data:	No	Copied to github as #: 22327
Description I have an issue in load layer definition file . When I create layer definition file as a new file, I can load it correctly. But, When I create it as a overwrite file, I can't load it. So, I have compare between new file and overwrite file. and I found difference in these files. In new file, <datasource> was written by Absolute filePath. In overwrite file, <datasource> was written by related filePath. thank you.		
Related issues: Related to QGIS Application - Bug report # 13925: Qlr-file saves datasource p... Closed 2015-12-01		

Associated revisions

Revision 9f7c3294 - 2016-02-25 10:51 PM - Jürgen Fischer

layer definition: always use relative paths regardless whether or not the file already exists (fixes #14340)

History

#1 - 2016-02-25 01:53 PM - Jürgen Fischer

- Status changed from Open to Closed

Fixed in changeset commit:"9f7c32944cf468f0da24f444c514fa90cf233841".

#2 - 2016-02-25 01:54 PM - Jürgen Fischer

- Status changed from Closed to In Progress

The file references in the qlr are relative to the position of the qlr itself - with the change it doesn't matter anymore if the qlr already existed.

#3 - 2016-02-25 04:25 PM - Jürgen Fischer

- Resolution set to fixed/implemented

- Status changed from In Progress to Closed

#4 - 2016-02-28 11:56 PM - Norihito Takahashi

Thank you so much !

#5 - 2016-03-03 12:15 AM - Norihito Takahashi

- File error.png added
- Assignee set to Jürgen Fischer
- Target version set to Version 2.14

I use QGIS in japanese. and, I have occurred an issue at qlr again...

I have created qlr in version Essen. but, it couldn't loaded correctly.
When I used in version Pisa, I could loaded qrl correctly.

So, I have compared qlr file created by Essen and created by Pisa.
I found difference that qlr file created by Essen was encoded "shit-jis" and japanese characters were garbled.
qlr file created by Pisa was encoded "utf-8" and japanese characters were correctly.
(I understood that file references are relative.)

#6 - 2017-09-22 10:05 AM - Jürgen Fischer

- Category set to Unknown

Files			
error.png	90.9 KB	2016-03-02	Norihito Takahashi