

QGIS Application - Feature request #17055

sld-reader doesn't use gap-size as interval

2017-08-24 10:47 AM - Paul van Genuchten

Status: Open	
Priority: Normal	
Assignee:	
Category: Symbology	
Pull Request or Patch supplied:	Resolution:
Easy fix?: Yes	Copied to github as #: 24954
Description	
<p>the sld writer writes the interval on a markerline as</p> <pre><lt;se:Gap> <lt;ogc:Literal>36</ogc:Literal> </se:Gap></pre> <p>however the reader doesn't seem to use this value and sets interval to 0</p> <p>note that Geoserver (SLD1.0) uses this format to indicate a markerline, this is loaded fine, however also here the interval is set to 0</p> <pre><LineSymbolizer> <Stroke> <GraphicStroke> <Graphic> <Mark> <WellKnownName>ttf://Wingdings#0x6C</WellKnownName> <Fill> <CssParameter name="fill">#FFFF73</CssParameter> </Fill> <Stroke> <CssParameter name="stroke">#FFFF73</CssParameter> </Stroke> </Mark> <Opacity>1</Opacity> <Size>18</Size> </Graphic> </GraphicStroke> <CssParameter name="stroke-dasharray">18 30</CssParameter> </Stroke> </LineSymbolizer></pre>	