

QGIS Application - Bug report #17413

Crash when using the identify tool in the "layer choice" mode

2017-11-07 04:44 PM - Andreas Neumann

Status:	Closed	
Priority:	High	
Assignee:		
Category:	GUI	
Affected QGIS version:	master	Regression?: No
Operating System:	Ubuntu	Easy fix?: No
Pull Request or Patch supplied:	No	Resolution:
Crashes QGIS or corrupts data:	Yes	Copied to github as #: 25310
Description		
In current QGIS master (commit:07cef67ead) - when I use the Identify tool with the "layer choice" mode and "Automatically open form if single feature is hit" - QGIS crashes just after the layer choice context menu shows up and before the form would show. Crash dump: ----- <pre>[Thread debugging using libthread_db enabled] Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1". 0x00007f68dfce8ea in __GI___waitpid (pid=15277, stat_loc=0x7ffff11009f4, options=0) at ../sysdeps/unix/sysv/linux/waitpid.c:29 29 ../sysdeps/unix/sysv/linux/waitpid.c: No such file or directory. [Current thread is 1 (Thread 0x7f68e423d1c0 (LWP 15124))] #0 0x00007f68dfce8ea in __GI___waitpid (pid=15277, stat_loc=0x7ffff11009f4, options=0) at ../sysdeps/unix/sysv/linux/waitpid.c:29 resultvar = 18446744073709551104 sc_cancel_oldtype = 0 #1 0x000055928446e5ca in qgisCrash(int) (signal=-1) at ../src/app/main.cpp:325 status = 8388644 pidstr = "--pid=15124\000\000\000\000\000\004\000\000\000\000\000\000\000\0362\te\340h\177\000" gdbpid = 15277 exename = "/usr/local/bin/qgis\000\377\177\000\000G\375\340h\177\000\000 \v\020\361\377\177\000\000 \f\020\361\377\177\000\000\001\000\000\000\000\000\000\000\000\000z\223k\340h\177\000\000\000\000\000n", '\000' <repeats 20 times>, "m!\027Z\323\032\360\000\311,\344h\177\000\000\060\350\340\207\222U\000\000p\351\340\207\222U\000\000\000m!\027Z\323\032\360 23\032\360\000\000\000\000\000\000\000\000\000\000\300\373x\210\222U\000\000\000\375x\210\222U\000\000 \f\000\340h\177\000\000\000\000\000\000\000\000\000\000\220\000\000\000\000\000\200\000\000\000\000\000\000\000\024\065 000\024\065\313\337h\177\000\000\021\000\000\000\000\000\000\000"... len = 19 #2 0x000055928446e8ca in myMessageOutput(QtMsgType, char const*) (type=QtFatalMsg, msg=0x55928878fbe8 "ASSERT: \"!isEmpty()\" in file /usr/include/x86_64-linux-gnu/qt5/QtCore/qvector.h, line 238") at ../src/app/main.cpp:389 #3 0x00007f68e063861a in () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5 #4 0x00007f68e063a0ee in QMessageLogger::fatal(char const*, ...) const () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5 #5 0x00007f68e0635357 in () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5 #6 0x00007f68ddd58768 in QVector<QPointF>::last() (this=0x7ffff1100e88) at /usr/include/x86_64-linux-gnu/qt5/QtCore/qvector.h:238 #7 0x00007f68ddd58240 in QVector<QPointF>::back() (this=0x7ffff1100e88) at /usr/include/x86_64-linux-gnu/qt5/QtCore/qvector.h:269 #8 0x00007f68ddd56c55 in QgsHighlight::paintPolygon(QPainter*, QVector<QVector<QgsPointXY> > const&) (this=0x7f68b8018cc0, p=0x7ffff11018f0, polygon=...) at ../src/gui/qgshighlight.cpp:245 curVertex = {xp = 223.65653983812081, yp = 108.93968809265061}</pre>		

```

sourceVertex = @0x5592859924c8: {static staticMetaObject = {d = {superdata = 0x0, stringdata = 0x7f68e2b6c820
<qt_meta_stringdata_QgsPointXY>, data = 0x7f68e2b6c880 <qt_meta_data_QgsPointXY>, static_metacall = 0x7f68e29fd5d4
<QgsPointXY::qt_static_metacall(QObject*, QMetaObject::Call, int, void**)>, relatedMetaObjects = 0x0, extradata = 0x0}}, mX =
2684947.0676741153, mY = 1223224.3434506613}
__for_range = @0x559285b13018: {d = 0x5592859924b0}
__for_begin = 0x5592859924c8
__for_end = 0x5592859940c8
ring = {<QVector<QPointF>> = {d = 0x559288a44f00}, <No data fields>}
lastVertex = {xp = 0, yp = 0}
sourceRing = @0x559285b13018: {d = 0x5592859924b0}
__for_range = @0x7fff1100fb0: {d = 0x559285b13000}
__for_begin = 0x559285b13018
__for_end = 0x559285b13020
path = {d_ptr = {d = 0x0}}
#9 0x00007f68ddd57158 in QgsHighlight::paint(QPainter*) (this=0x7f68b8018cc0, p=0x7fff11018f0) at
../src/gui/qgshighlight.cpp:313
#10 0x00007f68ddda75c4 in QgsMapCanvasItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
(this=0x7f68b8018cc0, painter=0x7fff11018f0, option=0x55928543e2e8, widget=0x5592859800f0) at
../src/gui/qgsmapcanvasitem.cpp:52
#11 0x00007f68e18afcb6 in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#12 0x00007f68e18b02c8 in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#13 0x00007f68e18b0aba in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#14 0x00007f68e18d3716 in QGraphicsView::paintEvent(QPaintEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#15 0x00007f68ddd99749 in QgsMapCanvas::paintEvent(QPaintEvent*) (this=0x559285775b30, e=0x7fff1101f00) at
../src/gui/qgsmapcanvas.cpp:1470
#16 0x00007f68e15e7dc8 in QWidget::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#17 0x00007f68e16c72de in QFrame::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#18 0x00007f68e18d224b in QGraphicsView::viewportEvent(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#19 0x00007f68e082cacc in QApplicationPrivate::sendThroughObjectEventFilters(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#20 0x00007f68e15a7445 in QApplicationPrivate::notify_helper(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#21 0x00007f68e15aed34 in QApplication::notify(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#22 0x00007f68e2304a63 in QgsApplication::notify(QObject*, QEvent*) (this=0x7fff1104e90, receiver=0x5592859800f0,
event=0x7fff1101f00) at ../src/core/qgsapplication.cpp:316
done = true
__FUNCTION__ = "notify"
#23 0x00007f68e082cde8 in QApplication::notifyInternal2(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#24 0x00007f68e15e0f6a in QWidgetPrivate::sendPaintEvent(QRegion const&) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#25 0x00007f68e15e152a in QWidgetPrivate::drawWidget(QPaintDevice*, QRegion const&, QPoint const&, int, QPainter*,
QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#26 0x00007f68e15e2190 in QWidgetPrivate::paintSiblingsRecursive(QPaintDevice*, QList<QObject*> const&, int, QRegion
const&, QPoint const&, int, QPainter*, QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#27 0x00007f68e15e1136 in QWidgetPrivate::drawWidget(QPaintDevice*, QRegion const&, QPoint const&, int, QPainter*,
QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#28 0x00007f68e15e2190 in QWidgetPrivate::paintSiblingsRecursive(QPaintDevice*, QList<QObject*> const&, int, QRegion
const&, QPoint const&, int, QPainter*, QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#29 0x00007f68e15e1136 in QWidgetPrivate::drawWidget(QPaintDevice*, QRegion const&, QPoint const&, int, QPainter*,
QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#30 0x00007f68e15e2190 in QWidgetPrivate::paintSiblingsRecursive(QPaintDevice*, QList<QObject*> const&, int, QRegion
const&, QPoint const&, int, QPainter*, QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#31 0x00007f68e15e1136 in QWidgetPrivate::drawWidget(QPaintDevice*, QRegion const&, QPoint const&, int, QPainter*,
QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5

```

```

#32 0x00007f68e15e2190 in QWidgetPrivate::paintSiblingsRecursive(QPaintDevice*, QList<QObject*> const&, int, QRegion
const&, QPoint const&, int, QPainter*, QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#33 0x00007f68e15e1136 in QWidgetPrivate::drawWidget(QPaintDevice*, QRegion const&, QPoint const&, int, QPainter*,
QWidgetBackingStore*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#34 0x00007f68e15b6a84 in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#35 0x00007f68e15b6cc5 in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#36 0x00007f68e15d053f in QWidgetPrivate::syncBackingStore() () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#37 0x00007f68e15e7f38 in QWidget::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#38 0x00007f68e16d5bab in QMainWindow::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#39 0x00007f68e32b24f3 in QgisApp::event(QEvent*) (this=0x5592856b71a0, event=0x55928869b290) at
../src/app/qgisapp.cpp:1580
    done = false
#40 0x00007f68e15a746c in QApplicationPrivate::notify_helper(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#41 0x00007f68e15aed34 in QApplication::notify(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#42 0x00007f68e2304a63 in QgsApplication::notify(QObject*, QEvent*) (this=0x7ffff1104e90, receiver=0x5592856b71a0,
event=0x55928869b290) at ../src/core/qgsapplication.cpp:316
    done = true
    __FUNCTION__ = "notify"
#43 0x00007f68e082cde8 in QCoreApplication::notifyInternal2(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#44 0x00007f68e082f55d in QCoreApplicationPrivate::sendPostedEvents(QObject*, int, QThreadData*) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#45 0x00007f68e18a3df2 in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#46 0x00007f68e18a8f79 in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#47 0x00007f68e085c452 in QObject::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#48 0x00007f68e18b43db in QGraphicsScene::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#49 0x00007f68e15a746c in QApplicationPrivate::notify_helper(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#50 0x00007f68e15aed34 in QApplication::notify(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#51 0x00007f68e2304a63 in QgsApplication::notify(QObject*, QEvent*) (this=0x7ffff1104e90, receiver=0x559285980a00,
event=0x559289e1dfd0) at ../src/core/qgsapplication.cpp:316
    done = true
    __FUNCTION__ = "notify"
#52 0x00007f68e082cde8 in QCoreApplication::notifyInternal2(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#53 0x00007f68e082f55d in QCoreApplicationPrivate::sendPostedEvents(QObject*, int, QThreadData*) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#54 0x00007f68e0885e53 in () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#55 0x00007f68d53edfb7 in g_main_context_dispatch () at /lib/x86_64-linux-gnu/libglib-2.0.so.0
#56 0x00007f68d53ee1f0 in () at /lib/x86_64-linux-gnu/libglib-2.0.so.0
#57 0x00007f68d53ee27c in g_main_context_iteration () at /lib/x86_64-linux-gnu/libglib-2.0.so.0
#58 0x00007f68e088547f in QEventDispatcherGlib::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#59 0x00007f68e082ae3a in QEventLoop::exec(QFlags<QEventLoop::ProcessEventsFlag>) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#60 0x00007f68e1700f60 in QMenu::exec(QPoint const&, QAction*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#61 0x00007f68ddd65c97 in QgsIdentifyMenu::exec(QList<QgsMapToolIdentify::IdentifyResult> const&, QPoint)
(this=0x559285cf0470, idResults=..., pos=...) at ../src/gui/qgsidentifymenu.cpp:134
    returnResults = {<QListSpecialMethods<QgsMapToolIdentify::IdentifyResult>> = {<No data fields>}, {p = {static shared_null
= {ref = {atomic = {_q_value = {<std::atomic_base<int>> = {static _S_alignment = 4, _M_i = -1}, <No data fields>}}}, alloc = 0,
begin = 0, end = 0, array = {0x0}}, d = 0x7f68e091ca00 <QListData::shared_null>}, d = 0x7f68e091ca00
<QListData::shared_null>}}
    singleLayer = false
    count = 3

```

```

it = {c = {d = 0x559287bef510}, i = {i = 0x559287bef518}, n = {i = 0x559288361420}}
selectedAction = 0x1d
externalAction = 160
#62 0x00007f68dddc3254 in QgsMapToolIdentify::identify(int, int, QgsMapToolIdentify::IdentifyMode, QList<QgsMapLayer*>
const&, QFlags<QgsMapToolIdentify::Type>) (this=0x559285cee840, x=538, y=249,
mode=QgsMapToolIdentify::LayerSelection, layerList=..., layerType=...) at ./src/gui/qgsmaptoolidentify.cpp:114
    results = {<QListSpecialMethods<QgsMapToolIdentify::IdentifyResult>> = {<No data fields>}, {p = {static shared_null = {ref =
{atomic = {_q_value = {<std::__atomic_base<int> = {static _S_alignment = 4, _M_i = -1}, <No data fields>}}}, alloc = 0, begin =
0, end = 0, array = {0x0}}, d = 0x559293bc57a0}, d = 0x559293bc57a0}}
    globalPos = {xp = 878, yp = 465}
    results = {<QListSpecialMethods<QgsMapToolIdentify::IdentifyResult>> = {<No data fields>}, {p = {static shared_null = {ref =
{atomic = {_q_value = {<std::__atomic_base<int> = {static _S_alignment = 4, _M_i = -1}, <No data fields>}}}, alloc = 0, begin =
0, end = 0, array = {0x0}}, d = 0x7f68e091ca00 <QListData::shared_null>}, d = 0x7f68e091ca00 <QListData::shared_null>}}
#63 0x00007f68dddc2e48 in QgsMapToolIdentify::identify(int, int, QgsMapToolIdentify::IdentifyMode,
QFlags<QgsMapToolIdentify::Type>) (this=0x559285cee840, x=538, y=249, mode=QgsMapToolIdentify::DefaultQgsSetting,
layerType=...) at ./src/gui/qgsmaptoolidentify.cpp:91
#64 0x00007f68e3543a0d in QgsMapToolIdentifyAction::canvasReleaseEvent(QgsMapMouseEvent*) (this=0x559285cee840,
e=0x559285861370) at ./src/app/qgsmaptoolidentifyaction.cpp:131
    extendedMenu = false
    mode = QgsMapToolIdentify::DefaultQgsSetting
    results = {<QListSpecialMethods<QgsMapToolIdentify::IdentifyResult>> = {<No data fields>}, {p = {static shared_null = {ref =
{atomic = {_q_value = {<std::__atomic_base<int> = {static _S_alignment = 4, _M_i = -1}, <No data fields>}}}, alloc = 0, begin =
0, end = 0, array = {0x0}}, d = 0x559285861370}, d = 0x559285861370}}
#65 0x00007f68ddd99551 in QgsMapCanvas::mouseReleaseEvent(QMouseEvent*) (this=0x559285775b30, e=0x7ffff1104360)
at ./src/gui/qgsmapcanvas.cpp:1434
    me = std::unique_ptr<QgsMapMouseEvent> containing 0x559285861370
    __FUNCTION__ = "mouseReleaseEvent"
#66 0x00007f68e15e7dc8 in QWidget::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#67 0x00007f68e16c72de in QFrame::event(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#68 0x00007f68e18d224b in QGraphicsView::viewportEvent(QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#69 0x00007f68e082cacc in QCoreApplicationPrivate::sendThroughObjectEventFilters(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#70 0x00007f68e15a7445 in QApplicationPrivate::notify_helper(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#71 0x00007f68e15af28f in QApplication::notify(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#72 0x00007f68e2304a63 in QgsApplication::notify(QObject*, QEvent*) (this=0x7ffff1104e90, receiver=0x5592859800f0,
event=0x7ffff1104360) at ./src/core/qgsapplication.cpp:316
    done = true
    __FUNCTION__ = "notify"
#73 0x00007f68e082cde8 in QCoreApplication::notifyInternal2(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#74 0x00007f68e15ae262 in QApplicationPrivate::sendMouseEvent(QWidget*, QMouseEvent*, QWidget*, QWidget*,
QWidget**, QPointer<QWidget>&, bool) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#75 0x00007f68e160294b in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#76 0x00007f68e1604fba in () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#77 0x00007f68e15a746c in QApplicationPrivate::notify_helper(QObject*, QEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#78 0x00007f68e15aed34 in QApplication::notify(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Widgets.so.5
#79 0x00007f68e2304a63 in QgsApplication::notify(QObject*, QEvent*) (this=0x7ffff1104e90, receiver=0x559287a671f0,
event=0x7ffff11047d0) at ./src/core/qgsapplication.cpp:316
    done = true
    __FUNCTION__ = "notify"
#80 0x00007f68e082cde8 in QCoreApplication::notifyInternal2(QObject*, QEvent*) () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#81 0x00007f68e0debf43 in QGuiApplicationPrivate::processMouseEvent(QWindowSystemInterfacePrivate::MouseEvent*) () at

```

```

/usr/lib/x86_64-linux-gnu/libQt5Gui.so.5
#82 0x00007f68e0deda25 in
QGuiApplicationPrivate::processWindowSystemEvent(QWindowSystemInterfacePrivate::WindowSystemEvent*) () at
/usr/lib/x86_64-linux-gnu/libQt5Gui.so.5
#83 0x00007f68e0dc5cab in QWindowSystemInterface::sendWindowSystemEvents(QFlags<QEventLoop::ProcessEventsFlag>)
() at /usr/lib/x86_64-linux-gnu/libQt5Gui.so.5
#84 0x00007f68c10375a0 in () at /usr/lib/x86_64-linux-gnu/libQt5XcbQpa.so.5
#85 0x00007f68d53edfb7 in g_main_context_dispatch () at /lib/x86_64-linux-gnu/libglib-2.0.so.0
#86 0x00007f68d53ee1f0 in () at /lib/x86_64-linux-gnu/libglib-2.0.so.0
#87 0x00007f68d53ee27c in g_main_context_iteration () at /lib/x86_64-linux-gnu/libglib-2.0.so.0
#88 0x00007f68e088547f in QEventDispatcherGlib::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#89 0x00007f68e082ae3a in QEventLoop::exec(QFlags<QEventLoop::ProcessEventsFlag>) () at
/usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#90 0x00007f68e0833da4 in QCoreApplication::exec() () at /usr/lib/x86_64-linux-gnu/libQt5Core.so.5
#91 0x0000559284474b43 in main(int, char**) (argc=3, argv=0x7ffff1105288) at ./src/app/main.cpp:1344
    profile = 0x5592853c8f20
    presetStyle = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
    rootProfileFolder = {static null = {<No data fields>}, d = 0x5592853c9de0}
    myLocaleOverrideFlag = false
    qgistor = <incomplete type>
    w = 600
    mySplashPath = {static null = {<No data fields>}, d = 0x7f68e2a85e60
<QgsApplication::splashPath()::{lambda()#1}::operator()() const::qstring_literal>}
    h = 300
    mypSplash = 0x5592854b50a0
    qgis = 0x5592856b71a0
    retval = 2
    manager = {<QObject> = {<No data fields>}, static staticMetaObject = {d = {superdata = 0x7f68e0cdca00
<QObject::staticMetaObject>, stringdata = 0x7f68e2b86140 <qt_meta_stringdata_QgsUserProfileManager>, data =
0x7f68e2b861c0 <qt_meta_data_QgsUserProfileManager>, static_metacall = 0x7f68e2a21ae2
<QgsUserProfileManager::qt_static_metacall(QObject*, QMetaObject::Call, int, void**)>, relatedMetaObjects = 0x0, extradata =
0x0}}, mWatchProfiles = false, mWatcher = std::unique_ptr<QFileSystemWatcher> containing 0x0, mRootProfilePath = {static
null = {<No data fields>}, d = 0x5592853c9de0}, mUserProfile = std::unique_ptr<QgsUserProfile> containing 0x0, mSettings =
std::unique_ptr<QSettings> containing 0x5592853781c0}
    profileFolder = {static null = {<No data fields>}, d = 0x5592853c9d20}
    mySettings = {<QObject> = {<No data fields>}, static staticMetaObject = {d = {superdata = 0x7f68e0cdca00
<QObject::staticMetaObject>, stringdata = 0x7f68e2b75420 <qt_meta_stringdata_QgsSettings>, data = 0x7f68e2b75460
<qt_meta_data_QgsSettings>, static_metacall = 0x7f68e2a09ce8 <QgsSettings::qt_static_metacall(QObject*,
QMetaObject::Call, int, void**)>, relatedMetaObjects = 0x0, extradata = 0x0}}, static sGlobalSettingsPath = {static null = {<No
data fields>}, d = 0x5592854668d0}, mUserSettings = 0x559285472b10, mGlobalSettings = 0x559285493990,
mUsingGlobalArray = false}
    systemEnvVars = {d = 0x559285454480}
    activeStyleName = {static null = {<No data fields>}, d = 0x5592855fc470}
    i18nPath = {static null = {<No data fields>}, d = 0x55928555ab80}
    myUserLocale = {static null = {<No data fields>}, d = 0x5592855fb670}
    qttor = <incomplete type>
    myApp = {<QApplication> = {<No data fields>}, static staticMetaObject = {d = {superdata = 0x7f68e1c68020
<QApplication::staticMetaObject>, stringdata = 0x7f68e2b63100 <qt_meta_stringdata_QgsApplication>, data = 0x7f68e2b63260
<qt_meta_data_QgsApplication>, static_metacall = 0x7f68e29ef6fa <QgsApplication::qt_static_metacall(QObject*,
QMetaObject::Call, int, void**)>, relatedMetaObjects = 0x0, extradata = 0x0}}, static QGIS_ORGANIZATION_NAME =
0x7f68e2a85488 "QGIS", static QGIS_ORGANIZATION_DOMAIN = 0x7f68e2a8548d "qgis.org", static
QGIS_APPLICATION_NAME = 0x7f68e2a85496 "QGIS3", static mFileOpenEventReceiver29900 = 0x5592856b71a0, static

```

```

mFileOpenEventList29900 = {<QList<QString>> = {<QListSpecialMethods<QString>> = {<No data fields>}, {p = {static
shared_null = {ref = {atomic = {_q_value = {<std::__atomic_base<int>> = {static _S_alignment = 4, _M_i = -1}, <No data
fields>}}}, alloc = 0, begin = 0, end = 0, array = {0x0}}, d = 0x7f68e091ca00 <QListData::shared_null>}, d = 0x7f68e091ca00
<QListData::shared_null>}}, <No data fields>}, static mUIThemeName29900 = {static null = {<No data fields>}, d =
0x7f68e091a400 <QArrayData::shared_null>}, static mPrefixPath29900 = {static null = <same as static member of an already
seen type>, d = 0x559285469ea0}, static mPluginPath29900 = {static null = <same as static member of an already seen type>, d
= 0x559285466840}, static mPkgDataPath29900 = {static null = <same as static member of an already seen type>, d =
0x559285443750}, static mLibraryPath29900 = {static null = <same as static member of an already seen type>, d =
0x559285469a30}, static mLibexecPath29900 = {static null = <same as static member of an already seen type>, d =
0x559285469d50}, static mThemeName29900 = {static null = <same as static member of an already seen type>, d =
0x7f68e2a85a00 <QgsApplication::setUITheme(QString const&)::lambda()#2::operator()() const::qstring_literal>}, static
mDefaultSvgPaths29900 = {<QList<QString>> = {<QListSpecialMethods<QString>> = {<No data fields>}, {p = {static
shared_null = {ref = {atomic = {_q_value = {<std::__atomic_base<int>> = {static _S_alignment = 4, _M_i = -1}, <No data
fields>}}}, alloc = 0, begin = 0, end = 0, array = {0x0}}, d = 0x559285466b50}, d = 0x559285466b50}}, <No data fields>}, static
mSystemEnvVars29900 = {d = 0x559285454480}, static mConfigPath29900 = {static null = {<No data fields>}, d =
0x559285466510}, static mRunningFromBuildDir29900 = false, static mBuildSourcePath29900 = {static null = <same as static
member of an already seen type>, d = 0x7f68e091a400 <QArrayData::shared_null>}, static mBuildOutputPath29900 = {static null
= <same as static member of an already seen type>, d = 0x7f68e091a400 <QArrayData::shared_null>}, static
mGdalSkipList29900 = {<QList<QString>> = {<QListSpecialMethods<QString>> = {<No data fields>}, {p = {static shared_null =
{ref = {atomic = {_q_value = {<std::__atomic_base<int>> = {static _S_alignment = 4, _M_i = -1}, <No data fields>}}}, alloc = 0,
begin = 0, end = 0, array = {0x0}}, d = 0x7f68e091ca00 <QListData::shared_null>}, d = 0x7f68e091ca00
<QListData::shared_null>}}, <No data fields>}, static mMaxThreads29900 = -1, static mAuthDbDirPath29900 = {static null = {<No
data fields>}, d = 0x559285466510}, static sUserName = {static null = <same as static member of an already seen type>, d =
0x559285b7f780}, static sUserFullName = {static null = <same as static member of an already seen type>, d =
0x559285b78d70}, static sPlatformName = {static null = <same as static member of an already seen type>, d =
0x5592853ca660}, mlconCache = {d = 0x55928545d3f0}, mDataItemProviderRegistry = 0x5592864272c0, mAuthManager =
0x559285995590, mApplicationMembers = 0x55928543cd0, static sApplicationMembers = 0x0}

customizationsettings = 0x559285468c20
useCustomVars = false
myPixmap = <incomplete type>
__FUNCTION__ = "main"
mySnapshotFileName = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
configLocalStorageLocation = {static null = {<No data fields>}, d = 0x5592853ca0e0}
profileName = {static null = {<No data fields>}, d = 0x5592853caab0}
mySnapshotWidth = 800
mySnapshotHeight = 600
myHideSplash = false
mySettingsMigrationForce = false
mySkipVersionCheck = false
myRestoreDefaultWindowState = false
myRestorePlugins = true
myCustomization = true
dxfoutputFile = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
dxfsymbologyMode = QgsDxfExport::SymbolLayerSymbology
dxfscale = 50000
dxfencoding = {static null = {<No data fields>}, d = 0x55928447cf00 <main::lambda()#1::operator()() const::qstring_literal>}
dxfpreset = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
dxfextent = {mXmin = 0, mYmin = 0, mXmax = 0, mYmax = 0}
myInitialExtent = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
myTranslationCode = {static null = {<No data fields>}, d = 0x5592855bd0c0}
configpath = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
authdbdirectory = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
pythonfile = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}

```

```
customizationfile = {static null = {<No data fields>}, d = 0x7f68e091a400 <QArrayData::shared_null>}
globalsettingsfile = {static null = {<No data fields>}, d = 0x5592854668d0}
args = {<QList<QString>> = {<QListSpecialMethods<QString>> = {<No data fields>}, {p = {static shared_null = {ref = {atomic
= {_q_value = {<std::__atomic_base<int>> = {static _S_alignment = 4, _M_i = -1}, <No data fields>}}}, alloc = 0, begin = 0, end =
0, array = {0x0}}, d = 0x5592853c6390}, d = 0x5592853c6390}}, <No data fields>}
myUseGuiFlag = true
settings = {<QObject> = {<No data fields>}, static staticMetaObject = {d = {superdata = 0x7f68e0cdca00
<QObject::staticMetaObject>, stringdata = 0x7f68e2b75420 <qt_meta_stringdata_QgsSettings>, data = 0x7f68e2b75460
<qt_meta_data_QgsSettings>, static_metacall = 0x7f68e2a09ce8 <QgsSettings::qt_static_metacall(QObject*,
QMetaObject::Call, int, void**)>, relatedMetaObjects = 0x0, extradata = 0x0}}, static sGlobalSettingsPath = {static null = {<No
data fields>}, d = 0x5592854668d0}, mUserSettings = 0x559285378ea0, mGlobalSettings = 0x0, mUsingGlobalArray = false}
gdb returned 0
```

Associated revisions

Revision **dc7ec1e1** - 2017-11-08 02:37 PM - Matthias Kuhn

No need to crash when a user wants a highlight

Fix #17413

History

#1 - 2017-11-07 04:46 PM - Andreas Neumann

I should add that the Identify tool works fine if I change the mode from "Layer choice" to "active layer only".

#2 - 2017-11-08 03:25 PM - Anonymous

- % Done changed from 0 to 100
- Status changed from Open to Closed

Applied in changeset commit:qgis|dc7ec1e1ca927a9b45466df85e14fb4083f7b80e.

#3 - 2018-03-12 08:51 PM - Jürgen Fischer

- Description updated