

QGIS Application - Bug report #19180

Treating UUID like text

2018-06-12 03:28 PM - Rémi Desgrange

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	DB Manager	
Affected QGIS version:	3.0.3	Regression?: No
Operating System:	all	Easy fix?: No
Pull Request or Patch supplied:	No	Resolution: fixed/implemented
Crashes QGIS or corrupts data:	No	Copied to github as #: 27009
Description		
<p>I have layer from postgis and here are some call from qgis 3 (from 3.0.0 to qgis 3.0.3) that makes errors :</p> <pre>SELECT "id"::text FROM (SELECT DISTINCT "id" FROM "my_schema"."v_mylayer" WHERE "id" ILIKE '%41bbe618-5399-4ca1-a50c-4be1a0acb9d1%' ORDER BY "id") foo</pre> <p>(this is from postgresql logs)</p> <p>v_mylayer is a view. Postgresql 10.4, postgis 2.4. this error appends on all operating system, mac os, linux windows (7&10)</p>		

Associated revisions

Revision e3f63d88 - 2018-09-19 01:17 PM - Jürgen Fischer

postgres provider: cast to text in uniqueStringsMatching (fixes #19180)

History

#1 - 2018-09-19 10:45 AM - Rémi Desgrange

This bug is still present in 3.2.3, on all OS. It also break the ability to cut a linestring. Since it want to created a new uuid like `<uuid>_1`

#2 - 2018-09-19 01:19 PM - Jürgen Fischer

- % Done changed from 0 to 100

- Status changed from Open to Closed

Applied in changeset commit:qgis|e3f63d8811506791ec197b6356cb7e9c4059fe03.

#3 - 2018-09-19 01:20 PM - Jürgen Fischer

- Resolution set to fixed/implemented