

QGIS Application - Bug report #19426

QGIS 3 Database Styles Manager does not load default style nor recognizes any styles related to a layer

2018-07-16 05:40 PM - Jochen Schwarze

Status:	Closed	
Priority:	High	
Assignee:		
Category:	Symbology	
Affected QGIS version:	3.2	Regression?: No
Operating System:		Easy fix?: No
Pull Request or Patch supplied:		Resolution: worksforme
Crashes QGIS or corrupts data:		Copied to github as #: 27254
Description		
<p>Stumbled upon this issue with styles used in spatialite db. These seem to be queried by</p> <pre>SELECT id,styleName,description FROM layer_styles WHERE f_table_schema=NULL AND f_table_name='my_table' AND f_geometry_column='geometry' ORDER BY useasdefault DESC, update_time DESC</pre> <p>Executing this query in QGIS DB Manager delivers no results (but also throws no error as well).</p> <p>Correcting ...f_table_schema=NULL... to ...f_table_schema IS NULL... delivers the desired results.</p> <p>refer to https://gis.stackexchange.com/questions/289562/qgis-3-does-not-load-default-styles-from-spatialite-defined-in-qgis-2-18</p>		

History

#1 - 2019-01-27 08:28 AM - Alexander Bruy

- Operating System deleted (Windows 10)
- Status changed from Open to Feedback

Seems already fixed in 3.4 and master. Please test.

#2 - 2019-02-10 09:07 AM - Alexander Bruy

- Resolution set to worksforme
- Status changed from Feedback to Closed