# QGIS Application - Bug report #21495

## Deleting shapefiles from the browser panel does not delete all the files

2019-03-06 07:39 AM - Harrissou Santanna

Status: Closed Priority: Normal

Assignee:

Category: Browser

Affected QGIS version: 3.4.5Regression?:NoOperating System:Easy fix?:No

Pull Request or Patch supplied: Resolution: up/downstream

Crashes QGIS or corruptes data: Copied to github as #: 29312

### Description

I have a shapefile I deleted from the QGIS browser panel (right-click --> Delete file xxx).

While dbf, shx, shp and prj files have gone, it let me with cpg and qpj files. It could be nice to have them removed too.

#### **Related issues:**

Related to QGIS Application - Feature request # 17032: delete (or propose to)... Closed 2017-08-18

### History

### #1 - 2019-03-09 05:35 PM - Alessandro Pasotti

- Resolution set to up/downstream
- Status changed from Open to Closed

I'm afraid this goes upstream to OGR/GDAL: we are using OGR calls to delete the OGR layers: GDALDatasetDeleteLayer()

#### #2 - 2019-03-30 02:44 AM - Andrea Giudiceandrea

Alessandro Pasotti wrote:

I'm afraid this goes upstream to OGR/GDAL: we are using OGR calls to delete the OGR layers: GDALDatasetDeleteLayer()

It seems to me that this is true for .cpg files only.

The .qpj files are created by QGIS, not by GDAL/OGR, so they should be deleted by QGIS.

In fact QgsVectorFileWriter::deleteShapeFile() deletes .qpj files along with ".shp", ".shx", ".dbf", ".prj", ".qix" files.

#### #3 - 2019-03-30 12:07 PM - Andrea Giudiceandrea

Andrea Giudiceandrea wrote:

It seems to me that this is true for .cpg files only.

Just now this was super fast fixed <a href="https://github.com/OSGeo/gdal/issues/1405">https://github.com/OSGeo/gdal/issues/1405</a> in GDAL/OGR master <a href="https://github.com/OSGeo/gdal/commit/41d8da793ee9a5360ad4ec7e3d97ace2913e11c5">https://github.com/OSGeo/gdal/commit/41d8da793ee9a5360ad4ec7e3d97ace2913e11c5</a>

2025-12-15 1/2

The .qpj files are created by QGIS, not by GDAL/OGR, so they should be deleted by QGIS.

 $Anyway, now \ GDAL/OGR \ GDALDataset Delete Layer() \ / \ OGRShape Data Source:: Delete Layer(), in master, take care of deletion of .qpj files also \\ \underline{https://github.com/OSGeo/gdal/commit/391a0c719c83be1c51e92717cc730edcd110062b}$ 

### #4 - 2019-03-31 09:41 PM - Andrea Giudiceandrea

- Related to Feature request #17032: delete (or propose to) all files of a shapefile with browser added

### #5 - 2019-04-01 12:12 AM - Harrissou Santanna

Thanks Andrea for having reported upstream.

2025-12-15 2/2