

QGIS Application - Bug report #229

Assignments used as truth value in qgsproject.cpp

2006-08-06 06:21 PM - Mateusz Loskot -

Status:	Closed	
Priority:	Low	
Assignee:	Gary Sherman	
Category:	Project Loading/Saving	
Affected QGIS version:		Regression?: No
Operating System:	Linux	Easy fix?: No
Pull Request or Patch supplied:		Resolution: fixed
Crashes QGIS or corrupts data:		Copied to github as #: 10288
Description		
<p>I'm not sure what's the idea behind conditional statements in qgsproject.cpp file, in lines: 126, 204 and 274 where following comparisons are used:</p> <pre>} else if (nextProperty = currentProperty->find(keySequence.first())) {</pre> <p>but for me this seems to be a bug.</p> <p>Probably, this statement should look like:</p> <pre>} else if ((nextProperty == currentProperty->find(keySequence.first()))) {</pre> <p>or</p> <pre>} else if (0 == (nextProperty = currentProperty->find(keySequence.first()))) {</pre> <p>Additional note, I see the code around those lines is mostly a copy-paste, may be it's reasonable to put it to a separate class or function.</p>		

History

#1 - 2006-08-11 02:52 AM - Gavin Macaulay -

- Resolution set to fixed
- Status changed from Open to Closed

Applied to head