

QGIS Application - Bug report #2894

Mapserver export: mangles shapefile paths in mapfile (layerid=0)

2010-07-19 08:10 AM - Sandro Santilli

Status:	Closed	
Priority:	Low	
Assignee:	Richard Duivenvoorde	
Category:	Python plugins	
Affected QGIS version:		Regression?: No
Operating System:	All	Easy fix?: No
Pull Request or Patch supplied:		Resolution: fixed
Crashes QGIS or corrupts data:		Copied to github as #: 12954
Description		
When exporting a project file to mapserver's mapfile the paths to shapefiles (DATA "/path/...") gets written with a " layerid=0" substring appended, making them all unresolvable to mapserver. The substring seems to be also in the project file itself, and works fine there (<datasource>) just needs to be split before writing to mapfile.		

Associated revisions

Revision 014f5688 - 2010-07-19 05:28 PM - Jürgen Fischer

fix #2894

git-svn-id: <http://svn.osgeo.org/qgis/trunk/qgis@13937> c8812cc2-4d05-0410-92ff-de0c093fc19c

Revision 75ce1bce - 2010-07-19 05:28 PM - Jürgen Fischer

fix #2894

git-svn-id: <http://svn.osgeo.org/qgis/trunk@13937> c8812cc2-4d05-0410-92ff-de0c093fc19c

History

#1 - 2010-07-19 08:28 AM - Jürgen Fischer

- Resolution set to fixed
- Status changed from Open to Closed

fixed in commit:75ce1bce (SVN r13938).