## QGIS Application - Bug report #5282 crssync not executed in debian postinst nor when "make install" is run

2012-04-02 02:51 PM - Etienne Tourigny

Status:	Closed		
Priority:	Normal		
Assignee:			
Category:	Projection Support		
		Regression?:	Νο
Operating System:	Linux	Easy fix?:	No
Pull Request or Patch		Resolution:	fixed
Crashes QGIS or corru <b>ptis</b> data:		Copied to github as #:	15002
Description			
•••••			
the new crssync utility is not run in key moments - debian installs and 'make install'. It is important that it be executed in order to avoid			
many problems with crs assignment (see bug #4977)			
1)			
There is a statement in bug #4977 that crssync is run in post inst, but I can't find where			
I have examined the debian config files and I do not see any reference to "crssync", contrary to the osgeo4w install script.			
I have also built .deb files for 1.8 and there is nothing special in the (auto-generated) postinst scripts.			
2)			
crssync should be part of the "make install" scripts, because srs.db gets installed each time but any sync gets overwritten.			
cissyne should be part of the make install scripts, because sisted gets installed each time but any syne gets over written.			
3)			
Can crssync be back-ported to 1.7, or at least install an updated srs.db? (see bug #4977)			
Can dissynd be back-pulled to $1.7$ , or at least install an updated sistub? (see buy #4977)			
4) It would be good to have an interface in Ontione (CRS tab) to run "areaurae"			
It would be good to have an interface in Options (CRS tab) to run "crssync".			

## History

## #1 - 2012-04-02 03:28 PM - Jürgen Fischer

- Resolution set to fixed
- Status changed from Open to Closed

- call in postinst added in commit:1011198 and commit:520e488.

- AFAIK there won't be another release of 1.7

- only root can update the srs.db, so a UI wouldn't work (easily)

- not sure about running crssync on 'make install'

## #2 - 2012-04-02 04:42 PM - Etienne Tourigny

- File crssync-install.patch added

Jurgen - thanks

please consider this patch which adds CRS\_SYNC[=TRUE] option. After installing \*.db files, crssync is run.

This is disabled in the debian/rules file by adding -D CRS\_SYNC=FALSE (so it isn't done at package building but at postinst)

Files

crssync-install.patch

3.62 KB

2012-04-02

Etienne Tourigny