

QGIS Application - Bug report #7048

QGIS Mapserver Internal Server Error

2013-01-25 09:31 AM - dr -

Status:	Closed	
Priority:	High	
Assignee:	Marco Hugentobler	
Category:	QGIS Server	
Affected QGIS version:	master	Regression?: No
Operating System:	Ubuntu	Easy fix?: No
Pull Request or Patch supplied:	no	Resolution: worksforme
Crashes QGIS or corrupts data:	no	Copied to github as #: 16136
Description		
<p>Trying to run QGIS Mapserver on Ubuntu 12.04 (1.9.0+git20130123+595a45f~precise-ubuntugis1) installed from http://qgis.org/ubuntugis-nightly. Open web page http://localhost/cgi-bin/qgis_mapserv.fcgi?SERVICE=WMS&#38;VERSION=1.3.0&#38;REQUEST=GetCapabilities and get Internal Server Error. Apache logs:</p> <pre>[Sat Jan 26 00:29:55 2013] [warn] [client ::1] mod_fcgid: error reading data, FastCGI server closed connection [Sat Jan 26 00:29:55 2013] [error] [client ::1] Premature end of script headers: qgis_mapserv.fcgi [Sat Jan 26 00:29:55 2013] [error] [client ::1] File does not exist: /var/www/favicon.ico [Sat Jan 26 00:30:00 2013] [error] mod_fcgid: process /usr/lib/cgi-bin/qgis_mapserv.fcgi(6333) exit(communication error), get signal 6, possible coredump generated</pre>		

History

#1 - 2013-01-25 09:49 AM - dr -

If put *.qgs file into cgi-bin directory - all works fine. Is it normal behavior?

#2 - 2013-06-02 07:36 AM - Giovanni Manghi

- Resolution set to worksforme
- Status changed from Open to Closed

I guess you cannot ask for capabilities without specifying a project file (with &map=...). If a QGIS in in cgi-bin this is assumed as default.