

QGIS Application - Bug report #9015

API: Using a QgsVectorLayer from an unusable uri crashes QGIS

2013-11-06 06:36 AM - Bernhard Ströbl

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	Data Provider	
Affected QGIS version:	2.0.1	Regression?: No
Operating System:		Easy fix?: No
Pull Request or Patch supplied:	No	Resolution: invalid
Crashes QGIS or corrupts data:	Yes	Copied to github as #: 17670
Description		
In my Python plugin I create layers from PostGIS tables <pre># db is a valid QSql.QSqlDataBase object uri = QgsDataSourceURI() uri.setConnection(db.hostName(), "5432", db.databaseName(), db.userName(), db.password()) uri.setDataSource(schemaName, tableName, geomColumnName) vlayer = QgsVectorLayer(uri.uri(), displayName, "postgres") QgsMapLayerRegistry.instance().addMapLayers([vlayer])</pre> if I try to use this vlayer further in my script QGIS simply crashes. The cause seems to be that the user has no SELECT rights on the relation in question. IMHO the constructor of QgsVectorLayer should throw an error if the uri is somehow not valid.		

History

#1 - 2013-11-06 07:05 AM - Luigi Pirelli

try to use isValid() call before to use the layer.

<http://www.qgis.org/api/classQgsDataProvider.html#a1f805f593a0fa0be58102e278114858b>

#2 - 2013-11-06 07:24 AM - Bernhard Ströbl

- Resolution set to invalid

- Status changed from Open to Closed

Hi Luigi,

and thanks for the tip. I was studying the api doc for QgsVectorLayer up and down. I quickly checked and realized that you can use almost anything (e.g. none existing shp file) to instantiate a QgsVectorLayer but it's data provider is not valid then either.